

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** **Belt Dressing**
 - **Article number:** 86502
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

 - **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**

KENT (United Kingdom) Ltd
Forsyth House
Pitreavie Drive
Pitreavie Business Park
Dunfermline
Fife
KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm
Fax: +44 1383 620079
SDS@kent europe.com
- **1.4 Emergency telephone number:**

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.
 - **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**

Rosin
Hydrocarbons, C7, n-alkanes isoalkanes, cyclic
pentane
- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 1)

- H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements**
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe mist/vapours/spray.
 P211 Do not spray on an open flame or other ignition source.
 P280 Wear protective gloves / eye protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 68476-85-7 EINECS: 270-704-2	Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)). ⚠ Flam. Gas 1, H220; Press. Gas L, H280	25-50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes isoalkanes, cyclic ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30	pentane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	1-10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	Propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<5%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32	Rosin ⚠ Skin Sens. 1, H317	<5%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<5%
CAS: 78-78-4 EINECS: 201-142-8	methylbutane ⚠ Flam. Liq. 1, H224; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	<5%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****After inhalation**

Supply fresh air and call for doctor for safety reasons.
 In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Rinse out mouth.
 In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
 - Can form explosive gas-air mixtures.
 - Formation of toxic gases is possible during heating or in case of fire.
 - Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:**
 - Do not inhale explosion gases or combustion gases.
 - Wear self-contained breathing apparatus.
- **Additional information**
 - Cool endangered containers with water spray jet.
 - Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation
 - Keep away from ignition sources
- **6.2 Environmental precautions:**
 - Inform respective authorities in case product reaches water or sewage system.
 - Do not allow to enter drainage system, surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Send for recovery or disposal in suitable containers.
 - Dispose of contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling
 - See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
 - Do not spray on flames or red-hot objects.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
 - Store in cool location.
 - Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Store in cool, dry conditions in well sealed containers.
 - Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 3)

8.1 Control parameters**Components with limit values that require monitoring at the workplace:****68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).**

WEL Short-term value: 2180 mg/m³, 1250 ppm
 Long-term value: 1750 mg/m³, 1000 ppm
 Carc (if LPG contains > 0.1% of buta-1.3-diene)

109-66-0 pentaneWEL Long-term value: 1800 mg/m³, 600 ppm**67-63-0 Propan-2-ol**

WEL Short-term value: 1250 mg/m³, 500 ppm
 Long-term value: 999 mg/m³, 400 ppm

8050-09-7 Rosin

WEL Short-term value: 0.15 mg/m³
 Long-term value: 0.05 mg/m³
 Sen

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
 Long-term value: 1210 mg/m³, 500 ppm

78-78-4 methylbutaneWEL Long-term value: 1800 mg/m³, 600 ppm**DNELs****Hydrocarbons, C7, n-alkanes isoalkanes, cyclic**

Dermal	Long term local	149 mg/kg/day (Consumer)
	Long term systemic	300 mg/kg/day (Worker)
Inhalative	Long term systemic	2085 mg/m ³ (Worker)
	Long term-local	447 mg/m ³ (Consumer)

109-66-0 pentane

Oral	Long term systemic	214mg/kg bw/day (Consumer)
Dermal	Long term systemic	214mg/kg bw/day (Consumer)
		432mg/kg bw/day (Worker)
Inhalative	Long term systemic	643 mg/m ³ (Consumer)
		3000 mg/m ³ (Worker)

67-63-0 Propan-2-ol

Oral	Long term systemic	26 mg/kg bw/day (Consumer)
Dermal	Long term systemic	319mg/kg bw/day (Consumer)
		888mg/kg bw/day (Worker)
Inhalative	Long term systemic	89 mg/m ³ (Consumer)
		500 mg/m ³ (Worker)

8050-09-7 Rosin

Oral	Long term systemic	10 mg/kg/day (Consumer)
Dermal	Long term systemic	10 mg/kg/day (Consumer)
		17 mg/kg/day (Worker)
Inhalative	Long term systemic	35 mg/m ³ (Consumer)
		117 mg/m ³ (Worker)

67-64-1 Acetone

Oral	Long term systemic	62mg/kg bw/day (Consumer)
Dermal	Long term systemic	62mg/kg bw/day (Consumer)
		186mg/kg bw/day (Worker)
Inhalative	Long term systemic	200 mg/m ³ (Consumer)
		1210 mg/m ³ (Worker)
	Acute local	2420 mg/m ³ (Worker)

78-78-4 methylbutane

Oral	Long term systemic	214 mg/kg/day (Consumer)
Dermal	Long term systemic	214 mg/kg (Consumer)
		432 mg/kg (Worker)
Inhalative	Long term systemic	643 mg/m ³ (Consumer)
		3000 mg/m ³ (Worker)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 4)

· PNECs**109-66-0 pentane**

PNEC 0.23 mg/l (Aqua (freshwater))
 1.2 mg/kg (Freshwater sediment)
 3.60 mg/l (Sewage treatment plant)
 0.55 mg/kg (Soil)

67-63-0 Propan-2-ol

PNEC 140.9 mg/l (Aqua (freshwater))
 140.9 mg/l (Aqua (intermittent))
 140.9 mg/l (Aqua (marine water))
 552 mg/kg (Freshwater sediment)
 552 mg/kg (Marine water sediment)
 2251 mg/l (Sewage treatment plant) (Assessment factor 1)
 28 mg/kg (Soil)

8050-09-7 Rosin

PNEC 0.0016 mg/l (Aqua (freshwater))
 0.016 mg/l (Aqua (intermittent))
 0.00016 mg/l (Aqua (marine water))
 0.007 mg/kg (Freshwater sediment)
 0.0007 mg/kg (Marine water sediment)
 1000 mg/l (Sewage treatment plant)
 0.00045 mg/kg (Soil)

67-64-1 Acetone

PNEC 1.06 mg/l (Aqua (marine water))
 30.4 mg/kg (Freshwater sediment)
 3.04 mg/kg (Marine water sediment)
 29.5 mg/kg (Soil)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls**· Personal protective equipment****· General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.
 Take off immediately all contaminated clothing
 Wash hands during breaks and at the end of the work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

· Breathing equipment:

Only during spraying without adequate removal by suction.
 Filter AX/P2.

· Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level $\leq$ 480 min (level 6)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 5)

· **Body protection:** Protective work clothing. (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	Yellow-brown
Odour:	Solvent-like
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not applicable, as aerosol

· Flash point: Not applicable, as aerosol

· Inflammability (solid, gaseous) Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· Self-inflammability: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· Critical values for explosion:

Lower:	Not determined.
Upper:	Not determined.

· Vapour pressure: Not determined.

· Density at 25 °C 0.770 g/cm³

· Relative density Not determined.

· Vapour density Not determined.

· Evaporation rate Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

dynamic:	Not determined.
kinematic:	Not determined.

· Solvent content:

Organic solvents: 588 G/L VOC

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **10.3 Possibility of hazardous reactions** No dangerous reactions known· **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.· **10.5 Incompatible materials:** No further relevant information available.

· 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxideGB
(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

· **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

	IC50	<10 mg/l (Algae)
109-66-0 pentane		
Oral	LD50	2001.0 mg/kg (Rat)
Dermal	LD50	2001.0 mg/kg (Rat)
67-63-0 Propan-2-ol		
Oral	LD50	4570 mg/kg (Rat)
Dermal	LD50	13400 mg/kg (Rabbit)
Inhalative	LC50 (4 hr)	30 mg/m3 (Rat)
8050-09-7 Rosin		
Oral	LD50	7600 mg/kg (Rat)
Dermal	LD50	2000.1 mg/kg (Rat)
67-64-1 Acetone		
Oral	LD50	5800 mg/kg (Rat)
Dermal	LD50	20000 mg/kg (Rabbit)
Inhalative	LC50 (4 hr)	76.0 mg/m3 (Rat)

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

· **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause drowsiness or dizziness.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxicity:

Hydrocarbons, C7, n-alkanes isoalkanes, cyclic

EC50 (48 hr)	3 mg/l (Daphnia magna)
LC50 (96 hr)	<10 mg/l (Fish)
	> 13.4 mg/l (Oncorhynchus mykiss)
NOEC	1.53 mg/l (Oncorhynchus mykiss) (28 days)
NOEC (21 days)	1 mg/l (Daphnia magna)
109-66-0 pentane	
EC50	10.7 mg/l (Pseudokirchneriella subcapitata) (72 hours)
EC50 (48 hr)	2.7 mg/l (Daphnia magna)
LC50 (96 hr)	4.26 mg/l (Oncorhynchus mykiss)
NOEC (72 hr)	7.51 mg/l (Pseudokirchneriella subcapitata)
67-63-0 Propan-2-ol	
EC50 (48 hr)	13299 mg/l (Daphnia magna)
LC50 (24 hr)	9714 mg/l (Daphnia magna)
LC50 (96 hr)	4200 mg/l (FSH) (dynamic)
	9640 mg/l (Pimephales promelas)
LOEC (8 days)	1000 mg/l (Algae)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 7)

67-64-1 Acetone

EC50 (48 hr)	39 mg/l (Daphnia magna)
LC50 (96 hr)	8300 mg/l (Fish)

78-78-4 methylbutane

EC50 (48 hr)	2.3 mg/l (Daphnia magna)
EC50 (72 hr)	10.7 mg/l (Selenastrum capricornutum)
LC50 (96 hr)	4.26 mg/l (Oncorhynchus mykiss)

- **12.2 Persistence and degradability** Moderately /partly biodegradable
- **12.3 Bioaccumulative potential** Does not accumulate in organisms
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.
- **Label** 2.1
- **IMDG, IATA**
- 
- **Class** 2.1
- **Label** 2.1

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 8)

· 14.4 Packing group	
· ADR	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Kemler Number:	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
NK	2.0

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 12

Revision: 22.02.2017

Trade name: Belt Dressing

(Contd. of page 9)

*H319 Causes serious eye irritation.**H336 May cause drowsiness or dizziness.**H411 Toxic to aquatic life with long lasting effects.*· **Department issuing data specification sheet:** Environment protection department· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas L: Gases under pressure – Liquefied gas

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **Data compared to the previous version altered.** *

GB